



UNLEADED GASOLINE

Safety Data Sheet

according to Regulation (EU) 2015/830

Revision date: 12/19/2016

Supersedes: 3/1/2011 Version: 6.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product form : Mixtures
Product name : UNLEADED GASOLINE

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Fuel

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Tedcastles Oil Products Ltd
Promenade Road
Dublin Port, Dublin 3 - Ireland
T 00353-1-8198000 - F 00353-1-8786635
safety@top.ie - www.top.ie

1.4. Emergency telephone number

Emergency number : 00353-1-8198000 (09:00 - 17:00 GMT)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 1	H224
Skin corrosion/irritation, Category 2	H315
Germ cell mutagenicity, Category 1B	H340
Carcinogenicity, Category 1A	H350
Reproductive toxicity, Category 2	H361
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity — Repeated exposure, Category 2	H373
Hazardous to the aquatic environment — Chronic Hazard, Category 2	H411

Full text of hazard classes and H-statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) :

Danger

Hazardous ingredients :

Gasoline; Toluene; Benzene

Hazard statements (CLP) :

H224 - Extremely flammable liquid and vapour
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness
H340 - May cause genetic defects
H350 - May cause cancer
H361 - Suspected of damaging fertility or the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (CLP) :

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

UNLEADED GASOLINE

Safety Data Sheet

according to Regulation (EU) 2015/830

P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical, lighting, ventilating equipment
P260 - Do not breathe mist, spray, vapours
P264 - Wash hands thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P273 - Avoid release to the environment
P280 - Wear protective clothing, protective gloves, eye protection
P302+P352 - IF ON SKIN: Wash with plenty of water
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P308+P313 - IF exposed or concerned: Get medical advice/attention
P312 - Call a poison center or doctor if you feel unwell
P321 - Specific treatment (see First aid measures on this label)
P332+P313 - If skin irritation occurs: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse
P370+P378 - In case of fire: Use carbon dioxide (CO₂), dry extinguishing powder, foam to extinguish
P391 - Collect spillage
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Gasoline	(CAS No) 86290-81-5 (EC no) 289-220-8 (EC index no) 232-89-220-8	90 - 100	Flam. Liq. 1, H224 Skin Irrit. 2, H315 Muta. 1B, H340 Carc. 1B, H350 Repr. 2, H361fd STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Toluene	(CAS No) 108-88-3 (EC no) 203-625-9 (EC index no) 601-021-00-3	< 15	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
ethanol	(CAS No) 64-17-5 (EC no) 200-578-6 (EC index no) 603-002-00-5	3 - 7	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H335
Hexane	(CAS No) 110-54-3 (EC no) 203-777-6 (EC index no) 601-037-00-0	> 2.5	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361f STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Benzene	(CAS No) 71-43-2 (EC no) 200-753-7 (EC index no) 601-020-00-8	< 2	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Muta. 1B, H340 Carc. 1A, H350 STOT RE 1, H372 Asp. Tox. 1, H304

UNLEADED GASOLINE

Safety Data Sheet

according to Regulation (EU) 2015/830

Specific concentration limits:

Name	Product identifier	Specific concentration limits
Hexane	(CAS No) 110-54-3 (EC no) 203-777-6 (EC index no) 601-037-00-0	(C >= 5) STOT RE 2, H373

Full text of H-statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

- First-aid measures general : IF exposed or concerned: Get medical advice/attention. If medical advice is needed, have product container or label at hand. Never give anything by mouth to an unconscious person.
- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
- First-aid measures after skin contact : If skin irritation occurs: Get medical advice/attention. Wash with plenty of soap and water. Take off immediately all contaminated clothing and wash it before reuse.
- First-aid measures after eye contact : If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- First-aid measures after ingestion : Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : May cause genetic defects. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.
- Symptoms/injuries after inhalation : May cause cancer by inhalation. May cause drowsiness or dizziness.
- Symptoms/injuries after skin contact : Causes skin irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

- Suitable extinguishing media : Carbon dioxide. Dry chemical. Foam.
- Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable liquid and vapour. Flammable vapours may accumulate in the container. Heavier than air, vapours may travel long distances along ground, ignite and flash back to source. Vapours may cause fire/explosion if source of ignition is present.
- Explosion hazard : May form flammable/explosive vapour-air mixture. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

5.3. Advice for firefighters

- Firefighting instructions : Cool adjacent structures and containers with water spray to protect and prevent ignition. Do not allow run-off from fire fighting to enter drains or water courses.
- Protection during firefighting : Wear a self contained breathing apparatus. Wear fire/flamm resistant/retardant clothing. EN469.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking. Do not breathe vapour. Do not breathe aerosol. Do not get in eyes, on skin, or on clothing. Ensure adequate ventilation. Use personal protective equipment as required.

6.1.1. For non-emergency personnel

- Protective equipment : Refer to section 8.2.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Refer to section 8.2.
- Emergency procedures : Ventilate area. Stop leak if safe to do so.

6.2. Environmental precautions

Do not discharge into drains or the environment. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Eliminate all ignition sources. Do not allow minor leaks or spills to accumulate on walking surfaces.

UNLEADED GASOLINE

Safety Data Sheet

according to Regulation (EU) 2015/830

Methods for cleaning up : Absorb and/or contain spill with inert material, then place in suitable container. Cover spill with non combustible material, e.g.: sand, earth, vermiculite.

6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.

Precautions for safe handling : No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Eliminate all ignition sources if safe to do so. Do not breathe vapours. Use only outdoors or in a well-ventilated area. Do not get in eyes, on skin, or on clothing. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment. Use explosion-proof lighting, electrical, ventilating equipment. Take precautionary measures against static discharge. Store in tightly closed, leak-proof containers. Comply with applicable regulations.

Storage conditions : Keep in fireproof place. Keep container tightly closed.

Incompatible products : Oxidizing agent. Reducing agents.

Incompatible materials : Heat sources.

Heat and ignition sources : Keep away from heat, sparks and flame.

Prohibitions on mixed storage : Incompatible materials.

Storage area : Store in dry, cool, well-ventilated area.

7.3. Specific end use(s)

Fuel.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Gasoline (86290-81-5)		
Czech Republic	Local name	Benzíny(technická směs uhlíků)
Czech Republic	Expoziční limity (PEL) (mg/m ³)	400 mg/m ³
Czech Republic	Expoziční limity (NPK-P) (mg/m ³)	1000 mg/m ³
Netherlands	Grenswaarde TGG 8H (mg/m ³)	240 mg/m ³
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	480 mg/m ³
Portugal	Local name	Gasolina
Portugal	OEL TWA (ppm)	300 ppm
Portugal	OEL STEL (ppm)	500 ppm
Spain	Local name	Gasolina
Spain	VLA-ED (ppm)	300 ppm
Spain	Notes	r (Esta sustancia tiene establecidas restricciones a la fabricación, la comercialización o el uso en los términos especificados en el "Reglamento (CE) nº 1907/2006 sobre Registro, Evaluación, Autorización y Restricción de sustancias y preparados químicos" (REACH) de 18 de diciembre de 2006 (DOUE L 369 de 30 de diciembre de 2006). Las restricciones de una sustancia pueden aplicarse a todos los usos o sólo a usos concretos. El anexo XVII del Reglamento REACH contiene la lista de todas las sustancias restringidas y especifica los usos que se han restringido).
USA - ACGIH	ACGIH TWA (ppm)	300 ppm
USA - ACGIH	ACGIH STEL (ppm)	500 ppm
USA - ACGIH	Remark (ACGIH)	URT & eye irr; CNS impair
Toluene (108-88-3)		
EU	Local name	Toluene
EU	IOELV TWA (mg/m ³)	192 mg/m ³
EU	IOELV TWA (ppm)	50 ppm

UNLEADED GASOLINE

Safety Data Sheet

according to Regulation (EU) 2015/830

Toluene (108-88-3)		
EU	IOELV STEL (mg/m ³)	384 mg/m ³
EU	IOELV STEL (ppm)	100 ppm
EU	Notes	skin
Austria	MAK (mg/m ³)	190 mg/m ³ (H,d)
Austria	MAK (ppm)	50 ppm (H,d)
Austria	MAK Short time value (mg/m ³)	380 mg/m ³ max. 4x15 min./Schicht, (H,d)
Austria	MAK Short time value (ppm)	100 ppm max. 4x15 min./Schicht, (H,d)
Belgium	Limit value (mg/m ³)	77 mg/m ³
Belgium	Limit value (ppm)	20 ppm
Belgium	Short time value (mg/m ³)	384 mg/m ³
Belgium	Short time value (ppm)	100 ppm
Belgium	Remark (BE)	D
Czech Republic	Local name	Toluen
Czech Republic	Expoziční limity (PEL) (mg/m ³)	200 mg/m ³
Czech Republic	Expoziční limity (PEL) (ppm)	53 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m ³)	500 mg/m ³
Czech Republic	Expoziční limity (NPK-P) (ppm)	130 ppm
Czech Republic	Remark (CZ)	D
Denmark	Local name	Toluen (Methylbenzen; Phenylmethan)
Denmark	Grænseværdie (langvarig) (mg/m ³)	94 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	25 ppm
Denmark	Grænseværdie (kortvarig) (mg/m ³)	188 mg/m ³
Denmark	Grænseværdie (kortvarig) (ppm)	50 ppm
Denmark	Anmærkninger (DK)	(1996); E (betyder, at stoffet har en EF-grænseværdi); H (betyder, at stoffet kan optages gennem huden)
Finland	Local name	Tolueneeni
Finland	HTP-arvo (8h) (mg/m ³)	81 mg/m ³
Finland	HTP-arvo (8h) (ppm)	25 ppm
Finland	HTP-arvo (15 min)	380 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	100 ppm
Finland	Huomautus (FI)	iho, melu
France	Local name	Toluène
France	VME (mg/m ³)	76.8 mg/m ³
France	VME (ppm)	20 ppm
France	KZGW (mg/m ³)	384 mg/m ³
France	KZGW (ppm)	100 ppm
France	Note (FR)	Valeurs réglementaires contraignantes; substance classée toxique pour la reproduction de catégorie 2; risque de pénétration percutanée
Germany	Local name	Toluol
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	190 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (ppm)	50 ppm
Germany	Remark (TRGS 900)	DFG,EU,H,Y
Germany	TRGS 903 (BGW)	3 mg/l o-Kresol (Urin; bei Langzeitexposition/Expositionsende bzw. Schichtende) 1 mg/l Toluol (Blut; Expositionsende bzw. Schichtende)
Hungary	Local name	TOLUOL
Hungary	AK-érték	190 mg/m ³
Hungary	CK-érték	380 mg/m ³
Hungary	Megjegyzések (HU)	b, i; II.2.
Ireland	OEL (8 hours ref) (mg/m ³)	192 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	50 ppm

UNLEADED GASOLINE

Safety Data Sheet

according to Regulation (EU) 2015/830

Toluene (108-88-3)		
Ireland	OEL (15 min ref) (mg/m ³)	384 mg/m ³
Ireland	OEL (15 min ref) (ppm)	100 ppm
Italy	Local name	Toluene
Italy	OEL TWA (mg/m ³)	192 mg/m ³
Italy	OEL TWA (ppm)	50 ppm
Latvia	Local name	Toluols (metilbenzols)
Latvia	OEL TWA (mg/m ³)	50 mg/m ³
Latvia	OEL TWA (ppm)	14 ppm
Latvia	OEL STEL (mg/m ³)	150 mg/m ³
Latvia	OEL STEL (ppm)	40 ppm
Lithuania	IPRV (mg/m ³)	192 mg/m ³
Lithuania	IPRV (ppm)	50 ppm
Lithuania	TPRV (mg/m ³)	384 mg/m ³
Lithuania	TPRV (ppm)	100 ppm
Lithuania	Remark (LT)	O
Netherlands	Local name	Toluene
Netherlands	Grenswaarde TGG 8H (mg/m ³)	150 mg/m ³
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	384 mg/m ³
Poland	Local name	Toluen
Poland	NDS (mg/m ³)	100 mg/m ³
Poland	NDSch (mg/m ³)	200 mg/m ³
Portugal	Local name	Tolueno
Portugal	OEL TWA (ppm)	50 ppm
Slovakia	NPHV (priemerná) (mg/m ³)	192 mg/m ³ (K)
Slovakia	NPHV (priemerná) (ppm)	50 ppm (K) 600 ppm (Toluén) 1.5 ppm (O-krezol) 2401 ppm (Kyselina hippurová)
Slovenia	Local name	toluen
Slovenia	OEL TWA (mg/m ³)	192 mg/m ³
Slovenia	OEL TWA (ppm)	50 ppm
Slovenia	OEL STEL (mg/m ³)	384 mg/m ³
Slovenia	OEL STEL (ppm)	100 ppm
Spain	Local name	Tolueno
Spain	VLA-ED (mg/m ³)	192 mg/m ³
Spain	VLA-ED (ppm)	50 ppm
Spain	VLA-EC (mg/m ³)	384 mg/m ³
Spain	VLA-EC (ppm)	100 ppm

UNLEADED GASOLINE

Safety Data Sheet

according to Regulation (EU) 2015/830

Toluene (108-88-3)		
Spain	Notes	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante. Para más información véase el Apartado 5 de este documento), VLB® (Agente químico que tiene Valor Límite Biológico específico en este documento), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país), r (Esta sustancia tiene establecidas restricciones a la fabricación, la comercialización o el uso en los términos especificados en el "Reglamento (CE) nº 1907/2006 sobre Registro, Evaluación, Autorización y Restricción de sustancias y preparados químicos" (REACH) de 18 de diciembre de 2006 (DOUE L 369 de 30 de diciembre de 2006). Las restricciones de una sustancia pueden aplicarse a todos los usos o sólo a usos concretos. El anexo XVII del Reglamento REACH contiene la lista de todas las sustancias restringidas y especifica los usos que se han restringido).
Sweden	Local name	Toluen
Sweden	nivågränsvärde (NVG) (mg/m ³)	192 mg/m ³
Sweden	nivågränsvärde (NVG) (ppm)	50 ppm
Sweden	kortidsvärde (KTV) (mg/m ³)	384 mg/m ³
Sweden	kortidsvärde (KTV) (ppm)	100 ppm
Sweden	Anmärkning (SE)	B (Ämnet kan orsaka hörselskada Exponering för ämnet nära det befintliga yrkeshygieniska gränsvärdet och vid samtidig exponering för buller nära insatsvärdet 80 dB kan orsaka hörselskada); H (Ämnet kan lätt upptas genom huden Det föreskrivna gränsvärdet bedöms ge tillräckligt skydd endast under förutsättning att huden är skyddad mot exponering för ämnet ifråga)
United Kingdom	WEL TWA (mg/m ³)	191 mg/m ³
United Kingdom	WEL TWA (ppm)	50 ppm
United Kingdom	WEL STEL (mg/m ³)	384 mg/m ³
United Kingdom	WEL STEL (ppm)	100 ppm
United Kingdom	Remark (WEL)	(Sk)
Norway	Local name	Toluen
Norway	Grenseverdier (AN) (mg/m ³)	94 mg/m ³
Norway	Grenseverdier (AN) (ppm)	25 ppm
Norway	Merknader (NO)	H (Kjemikalier som kan tas opp gjennom huden); E (EU har en veiledende grenseverdi for stoffet)
Switzerland	VME (mg/m ³)	190 mg/m ³
Switzerland	VME (ppm)	50 ppm 0.6 ppm toluolo (sangue; fine dell'esposizione / del turno) 0.5 ppm o-cresolo (urina; in caso di esposizione per molto tempo/fine dell'esposizione / del turno)
Switzerland	KZGW (mg/m ³)	760 mg/m ³ max. 4x15 min./turno
Switzerland	KZGW (ppm)	200 ppm max. 4x15 min./turno
Australia	TWA (mg/m ³)	191 mg/m ³
Australia	TWA (ppm)	50 ppm
Australia	STEL (mg/m ³)	384 mg/m ³

UNLEADED GASOLINE

Safety Data Sheet

according to Regulation (EU) 2015/830

Toluene (108-88-3)		
Australia	STEL (ppm)	100 ppm
USA - ACGIH	ACGIH TWA (ppm)	20 ppm
USA - ACGIH	Remark (ACGIH)	Visual impair; female repro;
Hexane (110-54-3)		
EU	Local name	n-Hexane
EU	IOELV TWA (mg/m ³)	72 mg/m ³
EU	IOELV TWA (ppm)	20 ppm
Austria	MAK (mg/m ³)	72 mg/m ³ (f)
Austria	MAK (ppm)	20 ppm (f)
Austria	MAK Short time value (mg/m ³)	288 mg/m ³ max. 4x15 min./Schicht, (f)
Austria	MAK Short time value (ppm)	80 ppm max. 4x15 min./Schicht, (f)
Belgium	Limit value (mg/m ³)	72 mg/m ³
Belgium	Limit value (ppm)	20 ppm
Czech Republic	Local name	n-Hexan
Czech Republic	Expoziční limity (PEL) (mg/m ³)	70 mg/m ³
Czech Republic	Expoziční limity (PEL) (ppm)	19.9 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m ³)	200 mg/m ³
Czech Republic	Expoziční limity (NPK-P) (ppm)	57 ppm
Czech Republic	Remark (CZ)	D, P
Denmark	Local name	n-Hexan
Denmark	Grænseværdie (langvarig) (mg/m ³)	72 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	20 ppm
Denmark	Anmærkninger (DK)	(2007); E (betyder, at stoffet har en EF-grænseværdi)
Finland	Local name	n-Heksaani
Finland	HTP-arvo (8h) (mg/m ³)	72 mg/m ³
Finland	HTP-arvo (8h) (ppm)	20 ppm
Finland	Huomautus (FI)	iho
France	Local name	n-Hexane
France	VME (mg/m ³)	72 mg/m ³
France	VME (ppm)	20 ppm
France	Note (FR)	Valeurs réglementaires contraignantes; substance classée toxique pour la reproduction de catégorie 2
Germany	Local name	n-Hexan
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	180 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (ppm)	50 ppm
Germany	Remark (TRGS 900)	DFG,EU,Y
Germany	TRGS 903 (BGW)	5 mg/l
Germany	Remark (TRGS 903)	2,5-Hexandion + 4,5-Dihydroxy-2-hexanon (Urin; Expositionsende bzw. Schichtende)
Hungary	Local name	n-HEXÁN
Hungary	AK-érték	72 mg/m ³
Hungary	Megjegyzések (HU)	b, i; II.1.
Ireland	OEL (8 hours ref) (mg/m ³)	72 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	20 ppm
Italy	Local name	n-Esano
Italy	OEL TWA (mg/m ³)	72 mg/m ³
Italy	OEL TWA (ppm)	20 ppm
Latvia	Local name	n-Heksāns
Latvia	OEL TWA (mg/m ³)	72 mg/m ³
Latvia	OEL TWA (ppm)	20 ppm
Lithuania	IPRV (mg/m ³)	72 mg/m ³
Lithuania	IPRV (ppm)	20 ppm

UNLEADED GASOLINE

Safety Data Sheet

according to Regulation (EU) 2015/830

Hexane (110-54-3)		
Lithuania	Remark (LT)	R
Netherlands	Local name	n-Hexaan
Netherlands	Grenswaarde TGG 8H (mg/m ³)	72 mg/m ³
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	144 mg/m ³
Poland	Local name	Heksan (n-heksan)
Poland	NDS (mg/m ³)	72 mg/m ³
Portugal	Local name	n-Hexano
Portugal	OEL TWA (ppm)	50 ppm
Slovakia	NPHV (priemerná) (mg/m ³)	72 mg/m ³
Slovakia	NPHV (priemerná) (ppm)	20 ppm 5 ppm (2,5-Hexándion a 4,5-dihydroxy-2-hexanón)
Slovenia	Local name	n-heksan
Slovenia	OEL TWA (mg/m ³)	72 mg/m ³
Slovenia	OEL TWA (ppm)	20 ppm
Spain	Local name	n-Hexano
Spain	VLA-ED (mg/m ³)	72 mg/m ³
Spain	VLA-ED (ppm)	20 ppm
Spain	Notes	VLB® (Agente químico que tiene Valor Límite Biológico específico en este documento), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país).
Sweden	Local name	n-Hexan
Sweden	nivågränsvärde (NVG) (mg/m ³)	90 mg/m ³
Sweden	nivågränsvärde (NVG) (ppm)	25 ppm
Sweden	kortidsvärde (KTV) (mg/m ³)	180 mg/m ³
Sweden	kortidsvärde (KTV) (ppm)	50 ppm
Sweden	Anmärkning (SE)	V (Vägledande kortidsgränsvärde ska användas som ett rekommenderat högsta värde som inte bör överskridas)
United Kingdom	WEL TWA (mg/m ³)	72 mg/m ³
United Kingdom	WEL TWA (ppm)	20 ppm
Norway	Local name	n-heksan
Norway	Grenseverdier (AN) (mg/m ³)	72 mg/m ³
Norway	Grenseverdier (AN) (ppm)	20 ppm
Norway	Merknader (NO)	R (Kjemikalier som skal betraktes som reproduksjonstoksiske); E (EU har en veiledende grenseverdi for stoffet)
Switzerland	VME (mg/m ³)	180 mg/m ³ max. 4x30 min./turno
Switzerland	VME (ppm)	50 ppm max. 4x30 min./turno 5 ppm 2,5-Hexandion + 4,5-Dihydroxy-2-hexanon (urina; fine dell'esposizione / del turno)
Switzerland	KZGW (mg/m ³)	1440 mg/m ³ max. 4x30 min./turno
Switzerland	KZGW (ppm)	400 ppm max. 4x30 min./turno
Australia	TWA (mg/m ³)	72 mg/m ³
Australia	TWA (ppm)	20 ppm
USA - ACGIH	ACGIH TWA (ppm)	50 ppm
USA - ACGIH	Remark (ACGIH)	CNS impair; peripheral neuropathy; eye irr; Skin; BEI
Benzene (71-43-2)		
EU	Local name	Benzene (Num:C1)
EU	IOELV TWA (mg/m ³)	3.25 mg/m ³

UNLEADED GASOLINE

Safety Data Sheet

according to Regulation (EU) 2015/830

Benzene (71-43-2)		
EU	IOELV TWA (ppm)	1 ppm
EU	Notes	skin. SCOEL Recommendations (Ongoing)
Austria	MAK (mg/m ³)	3.2 mg/m ³ (H, III A1)
Austria	MAK (ppm)	1 ppm (H, III A1)
Austria	MAK Short time value (mg/m ³)	12.8 mg/m ³ (H, III A1) max. 4x15 min./Schicht
Austria	MAK Short time value (ppm)	4 ppm (H, III A1) max. 4x15 min./Schicht
Belgium	Limit value (mg/m ³)	3.25 mg/m ³
Belgium	Limit value (ppm)	1 ppm
Belgium	Remark (BE)	C, D
Czech Republic	Local name	Benzen
Czech Republic	Expoziční limity (PEL) (mg/m ³)	3 mg/m ³
Czech Republic	Expoziční limity (PEL) (ppm)	0.94 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m ³)	10 mg/m ³
Czech Republic	Expoziční limity (NPK-P) (ppm)	3.1 ppm
Czech Republic	Remark (CZ)	D, P
Denmark	Local name	Benzen
Denmark	Grænseværdie (langvarig) (mg/m ³)	1.6 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	0.5 ppm
Denmark	Grænseværdie (kortvarig) (mg/m ³)	3.2 mg/m ³
Denmark	Grænseværdie (kortvarig) (ppm)	1 ppm
Denmark	Anmærkninger (DK)	(1996); E (betyder, at stoffet har en EF-grænseværdi); H (betyder, at stoffet kan optages gennem huden); K (betyder, at stoffet anses for at kunne være kræftfremkaldende)
Finland	Local name	Bentseeni
Finland	HTP-arvo (8h) (mg/m ³)	3.25 mg/m ³
Finland	HTP-arvo (8h) (ppm)	1 ppm
Finland	Huomautus (FI)	iho, liite 3 (SITOVAT RAJA-ARVOT) ja liite 9 (BENTSEENIPITOISUUDEN MITTAAMINEN)
France	Local name	Benzène
France	VME (mg/m ³)	3.25 mg/m ³
France	VME (ppm)	1 ppm
France	Note (FR)	Valeurs réglementaires contraignantes; substance classée cancérigène de catégorie 1a et mutagène de catégorie 1b; risque de pénétration percutanée
Hungary	Local name	BENZOL
Hungary	MK-érték	3 mg/m ³
Hungary	Megjegyzések (HU)	k, b, i; BEM
Ireland	OEL (8 hours ref) (mg/m ³)	3 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	1 ppm
Ireland	Notes (IE)	Sk, C1
Latvia	Local name	Benzols
Latvia	OEL TWA (mg/m ³)	3.25 mg/m ³
Latvia	OEL TWA (ppm)	1 ppm
Lithuania	IPRV (mg/m ³)	3.25 mg/m ³
Lithuania	IPRV (ppm)	1 ppm
Lithuania	TPRV (mg/m ³)	19 mg/m ³
Lithuania	TPRV (ppm)	6 ppm
Lithuania	Remark (LT)	K O; IPRV 3,25mg/m ³ (1 ppm) galios nuo 2003 06 27 (pagal direktyvos 97/42 EC 2 str. 1 dalyje nurodytą datą).
Netherlands	Local name	Benzeen
Netherlands	Grenswaarde TGG 8H (mg/m ³)	3.25 mg/m ³

UNLEADED GASOLINE

Safety Data Sheet

according to Regulation (EU) 2015/830

Benzene (71-43-2)		
Netherlands	Remark (MAC)	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een Haanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Poland	Local name	Benzen
Poland	NDS (mg/m ³)	1.6 mg/m ³
Portugal	Local name	Benzeno
Portugal	OEL TWA (ppm)	0.5 ppm
Portugal	OEL STEL (ppm)	2.5 ppm
Slovakia	NPHV (priemerná) (mg/m ³)	3.25 mg/m ³
Slovakia	NPHV (priemerná) (ppm)	1 ppm
Slovakia	Upozornenie (SK)	(Dokázaný karcinogén pre ľudí, Pravdepodobný mutagén)
Slovenia	Local name	benzen
Slovenia	OEL TWA (mg/m ³)	3.25 mg/m ³
Slovenia	OEL TWA (ppm)	1 ppm
Slovenia	OEL STEL (mg/m ³)	13 mg/m ³
Slovenia	OEL STEL (ppm)	4 ppm
Spain	Local name	Benceno
Spain	VLA-ED (mg/m ³)	3.25 mg/m ³
Spain	VLA-ED (ppm)	1 ppm
Spain	Notes	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante. Para más información véase el Apartado 5 de este documento), VLB® (Agente químico que tiene Valor Límite Biológico específico en este documento), v (Real Decreto 1124/2000, de 16 de junio (BOE nº 145 de 17 de junio de 2000), por el que se modifica el Real Decreto 665/1997, de 12 de mayo, sobre la protección de los trabajadores contra los riesgos relacionados con la exposición a agentes cancerígenos durante el trabajo), r (Esta sustancia tiene establecidas restricciones a la fabricación, la comercialización o el uso en los términos especificados en el "Reglamento (CE) nº 1907/2006 sobre Registro, Evaluación, Autorización y Restricción de sustancias y preparados químicos" (REACH) de 18 de diciembre de 2006 (DOUE L 369 de 30 de diciembre de 2006). Las restricciones de una sustancia pueden aplicarse a todos los usos o sólo a usos concretos. El anexo XVII del Reglamento REACH contiene la lista de todas las sustancias restringidas y especifica los usos que se han restringido).
Sweden	Local name	Bensen
Sweden	nivågränsvärde (NVG) (mg/m ³)	1.5 mg/m ³
Sweden	nivågränsvärde (NVG) (ppm)	0.5 ppm
Sweden	kortidsvärde (KTV) (mg/m ³)	9 mg/m ³
Sweden	kortidsvärde (KTV) (ppm)	3 ppm

UNLEADED GASOLINE

Safety Data Sheet

according to Regulation (EU) 2015/830

Benzene (71-43-2)		
Sweden	Anmärkning (SE)	C (Ämnet är cancerframkallande Risk för cancer finns även vid annan exponering än via inandning. För vissa cancerframkallande ämnen som inte har gränsvärden gäller förbud eller tillståndskrav enligt föreskrifterna om kemiska arbetsmiljörisker); H (Ämnet kan lätt upptas genom huden Det föreskrivna gränsvärdet bedöms ge tillräckligt skydd endast under förutsättning att huden är skyddad mot exponering för ämnet ifråga); V (Vägledande korttidsgränsvärde ska användas som ett rekommenderat högsta värde som inte bör överskridas)
United Kingdom	WEL TWA (mg/m ³)	3.25 mg/m ³
United Kingdom	WEL TWA (ppm)	1 ppm
United Kingdom	Remark (WEL)	Carc, Sk
Norway	Local name	Benzen
Norway	Grenseverdier (AN) (mg/m ³)	3 mg/m ³
Norway	Grenseverdier (AN) (ppm)	1 ppm
Norway	Merknader (NO)	G (EU har fastsatt en bindende grenseverdi for stoffet); H (Kjemikalier som kan tas opp gjennom huden); K (Kjemikalier som skal betraktes som kreftfremkallende)
Switzerland	VME (mg/m ³)	1.6 mg/m ³
Switzerland	VME (ppm)	0.5 ppm 25 ppm S-Phenylmerkaptursäure, Urin, b, 500 ppm t,t-Mukonsäure, Urin, b
USA - ACGIH	ACGIH TWA (ppm)	0.5 ppm
USA - ACGIH	ACGIH STEL (ppm)	2.5 ppm
USA - ACGIH	Remark (ACGIH)	Leukemia
ethanol (64-17-5)		
Austria	MAK (mg/m ³)	1900 mg/m ³
Austria	MAK (ppm)	1000 ppm
Austria	MAK Short time value (mg/m ³)	3800 mg/m ³ max. 3x60 min./Schicht (gemessen als Momentanwert)
Austria	MAK Short time value (ppm)	2000 ppm max. 3x60 min./Schicht (gemessen als Momentanwert)
Belgium	Limit value (mg/m ³)	1907 mg/m ³
Belgium	Limit value (ppm)	1000 ppm
Czech Republic	Local name	Ethanol
Czech Republic	Expoziční limity (PEL) (mg/m ³)	1000 mg/m ³
Czech Republic	Expoziční limity (PEL) (ppm)	530 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m ³)	3000 mg/m ³
Czech Republic	Expoziční limity (NPK-P) (ppm)	1590 ppm
Denmark	Local name	Ethanol (Ethylalkohol)
Denmark	Grænseværdie (langvarig) (mg/m ³)	1900 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	1000 ppm
Denmark	Grænseværdie (kortvarig) (mg/m ³)	3800 mg/m ³
Denmark	Grænseværdie (kortvarig) (ppm)	2000 ppm
Finland	Local name	Etanoli
Finland	HTP-arvo (8h) (mg/m ³)	1900 mg/m ³
Finland	HTP-arvo (8h) (ppm)	1000 ppm
Finland	HTP-arvo (15 min)	2500 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	1300 ppm
France	Local name	Alcool éthylique
France	VME (mg/m ³)	1900 mg/m ³
France	VME (ppm)	1000 ppm
France	KZGW (mg/m ³)	9500 mg/m ³
France	KZGW (ppm)	5000 ppm

UNLEADED GASOLINE

Safety Data Sheet

according to Regulation (EU) 2015/830

ethanol (64-17-5)		
Germany	Local name	Ethanol
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	960 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (ppm)	500 ppm
Hungary	Local name	ETIL-ALKOHOL
Hungary	AK-érték	1900 mg/m ³
Hungary	CK-érték	7600 mg/m ³
Ireland	OEL (15 min ref) (ppm)	1000 ppm
Latvia	Local name	Etilspirts (etanols)
Latvia	OEL TWA (mg/m ³)	1000 mg/m ³
Lithuania	IPRV (mg/m ³)	1000 mg/m ³
Lithuania	IPRV (ppm)	500 ppm
Lithuania	TPRV (mg/m ³)	1900 mg/m ³
Lithuania	TPRV (ppm)	1000 ppm
Netherlands	Local name	Ethanol
Netherlands	Grenswaarde TGG 8H (mg/m ³)	260 mg/m ³
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	1900 mg/m ³
Poland	Local name	Etanol (alkohol etylowy)
Poland	NDS (mg/m ³)	1900 mg/m ³
Portugal	Local name	Etanol (Álcool etílico)
Portugal	OEL TWA (ppm)	1000 ppm
Slovakia	NPHV (priemerná) (mg/m ³)	960 mg/m ³
Slovakia	NPHV (priemerná) (ppm)	500 ppm
Slovenia	Local name	etanol (etilalkohol)
Slovenia	OEL TWA (mg/m ³)	1900 mg/m ³
Slovenia	OEL TWA (ppm)	1000 ppm
Slovenia	OEL STEL (mg/m ³)	7600 mg/m ³
Slovenia	OEL STEL (ppm)	4000 ppm
Spain	Local name	Etanol (Alcohol etílico)
Spain	VLA-ED (mg/m ³)	1910 mg/m ³
Spain	VLA-ED (ppm)	1000 ppm
Spain	Notes	s,
Sweden	Local name	Etanol
Sweden	nivågränsvärde (NVG) (mg/m ³)	1000 mg/m ³
Sweden	nivågränsvärde (NVG) (ppm)	500 ppm
Sweden	kortidsvärde (KTV) (mg/m ³)	1900 mg/m ³
Sweden	kortidsvärde (KTV) (ppm)	1000 ppm
United Kingdom	WEL TWA (mg/m ³)	1920 mg/m ³
United Kingdom	WEL TWA (ppm)	1000 ppm
Norway	Local name	Etanol
Norway	Grenseverdier (AN) (mg/m ³)	950 mg/m ³
Norway	Grenseverdier (AN) (ppm)	500 ppm
Switzerland	VME (mg/m ³)	960 mg/m ³
Switzerland	VME (ppm)	500 ppm
Switzerland	KZGW (mg/m ³)	1920 mg/m ³
Switzerland	KZGW (ppm)	1000 ppm
Australia	TWA (mg/m ³)	1920 mg/m ³
Australia	TWA (ppm)	1000 ppm
USA - ACGIH	ACGIH TWA (mg/m ³)	1884 mg/m ³
USA - ACGIH	ACGIH TWA (ppm)	1000 ppm
USA - ACGIH	ACGIH STEL (ppm)	1000 ppm
USA - ACGIH	Remark (ACGIH)	URT irr

UNLEADED GASOLINE

Safety Data Sheet

according to Regulation (EU) 2015/830

8.2. Exposure controls

Appropriate engineering controls:

Avoid splashing. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure good ventilation of the work station. Proper grounding procedures to avoid static electricity should be followed. Use spark-/explosionproof appliances and lighting system.

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear suitable gloves resistant to chemical penetration. EN374

Eye protection:

Chemical goggles or safety glasses. EN166

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Approved respirator. EN 136/140

Environmental exposure controls:

Prevent leakage or spillage. Prevent contaminated water run-off.

Other information:

Do not eat, drink or smoke when using this product.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear.
Colour	: light yellow.
Odour	: Gasoline.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: 10 - 11
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 31 - 191 °C
Flash point	: -40 °C
Auto-ignition temperature	: 450 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable liquid and vapour
Vapour pressure	: 60 kPa @ 20 °C
Relative vapour density at 20 °C	: > 1
Relative density	: ≥ 0.75 @ 15 °C
Solubility	: Water: 0.01 g/l
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Lower explosive limit (LEL)	: 1.3 vol %
Upper explosive limit (UEL)	: 7.6 vol %

9.2. Other information

No additional information available

UNLEADED GASOLINE

Safety Data Sheet

according to Regulation (EU) 2015/830

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Extremely flammable liquid and vapour. May form flammable/explosive vapour-air mixture. Vapour could travel to source of ignition and flash back.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Sparks. Heat. Direct sunlight. Overheating. Open flame.

10.5. Incompatible materials

Reducing agents. Oxidizing agent.

10.6. Hazardous decomposition products

May release flammable gases. Carbon oxides (CO, CO₂). Nitrous fumes.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity : Not classified

Gasoline (86290-81-5)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5000 mg/m ³ 4 h

Toluene (108-88-3)	
LD50 oral rat	5580 mg/kg EU Method B.1 (Acute Toxicity (Oral))
LC50 inhalation rat (mg/l)	> 20 mg/l/4h OECD Guideline 403 (Acute Inhalation Toxicity)

Hexane (110-54-3)	
LD50 oral rat	30 g/kg OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 2000 mg/kg standard acute method
LC50 inhalation rat (ppm)	> 5000 OECD Guideline 403 (Acute Inhalation Toxicity)

Benzene (71-43-2)	
LD50 oral rat	5970 mg/kg OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 9.4 mg/kg OECD Guideline 402 (Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	43.7 mg/l/4h OECD Guideline 403 (Acute Inhalation Toxicity)

ethanol (64-17-5)	
LD50 oral rat	7060 mg/kg
LC50 inhalation rat (ppm)	20000 ppm 10 h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.

Toluene (108-88-3)	
LOAEL (inhalation, rat, gas, 90 days)	1250 ppmv/6h/day
NOAEL (oral, rat, 90 days)	625 mg/kg bodyweight/day EU Method B.26.
NOAEL (inhalation, rat, gas, 90 days)	300 ppmv/6h/day OECD Guideline 453

Benzene (71-43-2)	
LOAEL (oral, rat, 90 days)	25 mg/kg bodyweight/day OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEL (oral, rat, 90 days)	100 mg/kg bodyweight/day OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEL (inhalation, rat, gas, 90 days)	30 ppmv/6h/day OECD Guideline 412 / 413

Aspiration hazard : Not classified

UNLEADED GASOLINE

Safety Data Sheet

according to Regulation (EU) 2015/830

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - water : Toxic to aquatic life with long lasting effects.

Toluene (108-88-3)	
LC50 fish 1	5.5 mg/l
EC50 Daphnia 2	3.78 mg/l
ErC50 (algae)	134 mg/l
LOEC (chronic)	2.77 mg/l
NOEC chronic fish	1.39 mg/l
NOEC chronic crustacea	0.74 mg/l

Benzene (71-43-2)	
LC50 fish 1	5.3 mg/l OECD Guideline 203 (Fish, Acute Toxicity Test)
EC50 Daphnia 1	10 mg/l OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
ErC50 (algae)	100 mg/l OECD Guideline 201 (Alga, Growth Inhibition Test)
LOEC (chronic)	1.6 mg/l 32 d
NOEC chronic crustacea	3 mg/l

ethanol (64-17-5)	
LC50 fish 1	> 10000 mg/l <i>Oncorhynchus mykiss</i>
LC50 fish 2	> 13400 mg/l <i>Pimephales promelas</i>

12.2. Persistence and degradability

UNLEADED GASOLINE	
Persistence and degradability	May cause long-term adverse effects in the environment.

Gasoline (86290-81-5)	
Persistence and degradability	inherently biodegradable.
Biodegradation	90.35 % 28 d

Toluene (108-88-3)	
Persistence and degradability	Readily biodegradable.

Benzene (71-43-2)	
Persistence and degradability	Readily biodegradable.

ethanol (64-17-5)	
Persistence and degradability	Readily biodegradable.

12.3. Bioaccumulative potential

UNLEADED GASOLINE	
Bioaccumulative potential	Not established.

Toluene (108-88-3)	
Bioconcentration factor (BCF REACH)	90
Log Kow	2.73

Benzene (71-43-2)	
BCF fish 1	3.5 - 4.4
Bioconcentration factor (BCF REACH)	0
Log Pow	1.83

ethanol (64-17-5)	
Bioaccumulative potential	Not expected to bioaccumulate.

12.4. Mobility in soil

UNLEADED GASOLINE	
Ecology - soil	Not established.

12.5. Results of PBT and vPvB assessment

UNLEADED GASOLINE	
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
Component	
Toluene (108-88-3)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

UNLEADED GASOLINE

Safety Data Sheet

according to Regulation (EU) 2015/830

Component	
Benzene (71-43-2)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste disposal recommendations	: Do not burn empty packaging. Do not cut using a blowtorch. Dispose in a safe manner in accordance with local/national regulations. Do not pierce or burn, even after use.
Additional information	: Handle empty containers with care because residual vapours are flammable.
European List of Waste (LoW) code	: For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used. 13 07 02* - petrol

SECTION 14: TRANSPORT INFORMATION

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR)	: 1203
UN-No. (IMDG)	: 1203
UN-No. (IATA)	: 1203
UN-No. (ADN)	: 1203
UN-No. (RID)	: 1203

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: GASOLINE
Proper Shipping Name (IMDG)	: GASOLINE
Proper Shipping Name (IATA)	: Gasoline
Proper Shipping Name (ADN)	: GASOLINE
Proper Shipping Name (RID)	: GASOLINE
Transport document description (ADR)	: UN 1203 GASOLINE, 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS
Transport document description (IMDG)	: UN 1203 GASOLINE, 3, II, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS
Transport document description (IATA)	: UN 1203 Gasoline, 3, II, ENVIRONMENTALLY HAZARDOUS
Transport document description (ADN)	: UN 1203 GASOLINE, 3, II, ENVIRONMENTALLY HAZARDOUS
Transport document description (RID)	: UN 1203 GASOLINE, 3, II, ENVIRONMENTALLY HAZARDOUS

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR)	: 3
Danger labels (ADR)	: 3



IMDG

Transport hazard class(es) (IMDG)	: 3
Danger labels (IMDG)	: 3



IATA

Transport hazard class(es) (IATA)	: 3
-----------------------------------	-----

UNLEADED GASOLINE

Safety Data Sheet

according to Regulation (EU) 2015/830

Hazard labels (IATA) : 3



ADN

Transport hazard class(es) (ADN) : 3

Danger labels (ADN) : 3



RID

Transport hazard class(es) (RID) : 3

Danger labels (RID) : 3



14.4. Packing group

Packing group (ADR) : II

Packing group (IMDG) : II

Packing group (IATA) : II

Packing group (ADN) : II

Packing group (RID) : II

14.5. Environmental hazards

Dangerous for the environment : Yes

Marine pollutant : Yes

Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : F1

Special provisions (ADR) : 243, 534, 363, 664

Limited quantities (ADR) : 11

Excepted quantities (ADR) : E2

Packing instructions (ADR) : P001, IBC02, R001

Special packing provisions (ADR) : BB2

Mixed packing provisions (ADR) : MP19

Portable tank and bulk container instructions (ADR) : T4

Portable tank and bulk container special provisions (ADR) : TP1

Tank code (ADR) : LGBF

Tank special provisions (ADR) : TU9

Vehicle for tank carriage : FL

Transport category (ADR) : 2

Special provisions for carriage - Operation (ADR) : S2, S20

Hazard identification number (Kemler No.) : 33

UNLEADED GASOLINE

Safety Data Sheet

according to Regulation (EU) 2015/830

Orange plates



Tunnel restriction code (ADR) : D/E
EAC code : 3YE

- Transport by sea

Special provisions (IMDG) : 243, 363
Limited quantities (IMDG) : 1 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : E
Properties and observations (IMDG) : Immiscible with water.

- Air transport

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
Special provisions (IATA) : A100
ERG code (IATA) : 3H

- Inland waterway transport

Classification code (ADN) : F1
Special provisions (ADN) : 243, 363, 534
Limited quantities (ADN) : 1 L
Excepted quantities (ADN) : E2
Carriage permitted (ADN) : T
Equipment required (ADN) : PP, EX, A
Ventilation (ADN) : VE01
Number of blue cones/lights (ADN) : 1

- Rail transport

Classification code (RID) : F1
Special provisions (RID) : 243, 363, 534
Limited quantities (RID) : 1L
Excepted quantities (RID) : E2
Packing instructions (RID) : P001, IBC02, R001
Special packing provisions (RID) : BB2
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4
Portable tank and bulk container special provisions (RID) : TP1
Tank codes for RID tanks (RID) : LGBF
Special provisions for RID tanks (RID) : TU9
Transport category (RID) : 2
Colis express (express parcels) (RID) : CE7
Hazard identification number (RID) : 33

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

UNLEADED GASOLINE

Safety Data Sheet

according to Regulation (EU) 2015/830

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

Germany

VwVwS Annex reference : Water hazard class (WGK) 3, severe hazard to waters (Classification according to VwVwS, Annex 4)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : Gasoline, Benzene, ethanol are listed

SZW-lijst van mutagene stoffen : Gasoline, Benzene are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : ethanol is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : Hexane, ethanol are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Toluene, ethanol are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: OTHER INFORMATION

Abbreviations and acronyms:

	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population
	PBT: Persistent, Bioaccumulative, Toxic
	STEL: Short Term Exposure Limits
	TWA: Time Weighted Average
vPvB	Very Persistent and Very Bioaccumulative

Data sources : European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>.
Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition.
National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition.
REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
-------------------	---

UNLEADED GASOLINE

Safety Data Sheet

according to Regulation (EU) 2015/830

Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1A	Carcinogenicity, Category 1A
Carc. 1B	Carcinogenicity, Category 1B
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 1	Flammable liquids, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Muta. 1B	Germ cell mutagenicity, Category 1B
Repr. 2	Reproductive toxicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H224	Extremely flammable liquid and vapour
H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
H361d	Suspected of damaging the unborn child
H361f	Suspected of damaging fertility
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Flam. Liq. 1	H224	Expert judgment
Skin Irrit. 2	H315	Calculation method
Muta. 1B	H340	Calculation method
Carc. 1A	H350	Calculation method
Repr. 2	H361	Calculation method
STOT SE 3	H336	Calculation method
STOT RE 2	H373	Calculation method
Aquatic Chronic 2	H411	Calculation method

SDS prepared by:

The Redstone Group, LLC
6077 Frantz Rd
Suite 206
Dublin, Ohio USA 43016
www.redstonegrp.com
614.923.7472

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product